



Installation Instructions for Hot Fix 16 (A5T020)

Table of Contents

Overview	3
INSTALLATION	4
Post-Installation Instructions:.....	5
Initial Notes	5
Database Changes by Hotfix.....	6
Hotfix 1 Database Changes	6
Hotfix 2 Database Changes.....	7
Hotfix 3 Database Changes.....	7
Hotfix 4 Database Changes.....	7
Hotfix 5 Database Changes.....	8
Hotfix 6 Database Changes.....	9
Hotfix 7 Database Changes.....	9
Hotfix 8 Database Changes.....	9
Hotfix 9 Database Changes.....	9
Hotfix 10 Database Changes.....	9
Hotfix 10_ICF1 Database Changes.....	9
Hotfix 11 Database Changes.....	9
Hotfix 12 Database Changes.....	9
Hotfix 13 Database Changes.....	9
Hotfix 14 Database Changes.....	10
Hotfix 15 Database Changes.....	10
Hotfix 16 Database Changes.....	10
Capabilities Changes by Hotfix and Role	10
Hotfix-Configuration Process: Execute for each Business Unit	10
Pre-Hotfix-Configuration Steps	10
Hotfix-Configuration Steps.....	13
Have Authority to run DB DDL	14
Do Not Have Authority to run DB DDL.....	15
Post-Hotfix-Configuration Steps.....	19
Optional Configuration Steps.....	25
Microsoft SQL Server: Convert to nvarchar	25

A5Q019 Updates SAS Compliance Solutions Mid-Tier 7.1	25
Step 1: Re-build Web Applications	26
Step 2: Re-deploy Web Applications	26
Step 3: Apply New Groups and Capabilities to Metadata (if required)	27
Step 4: Reapply Business Unit Datasource Definitions.....	27
Step 5: Import AML Scenarios Package (if required).....	28
Step 6: Import CDD Rules Package (if required).....	29
Concluding Steps:	29
A6A006 Updates SAS Compliance Solutions LASR Configuration 7.1	29
A6H004 Updates SAS Compliance Solutions Mid-Tier LASR Configuration 7.1.....	33

Overview

Important Note: SAS Security Update 2022-06 is required to be installed along with this Hot fix. See <https://tshf.sas.com> for more information about the Security Update.

Hot fix **A5T020** addresses the issue(s) in **Compliance Solutions 7.1** as documented in the *Issue(s) Addressed* section of the hot fix download page:

<https://tshf.sas.com/techsup/download/hotfix/HF2/A5T.html#A5T020>

A5T020 is a "container" hot fix that contains the following "member" hot fixes which will update the software components as needed.

A5Q019 for **SAS Compliance Solutions Mid-Tier 7.1 – Updated in A5T020**

A5R018 for **SAS Compliance Solutions Server 7.1 – Updated in A5T020**

A6A006 for **SAS Compliance Solutions LASR Configuration 7.1 – Last updated in A5T006**

A6H004 for **SAS Compliance Solutions Mid-Tier LASR Configuration 7.1 – Last updated in A5T010**

See [What is a container hot fix?](#) in the Hot Fix FAQ for more information about container hot fixes.

Before applying this hot fix, follow the instructions in [SAS Note 35968](#) to generate a SAS Deployment Registry report, then verify that the appropriate product releases are installed on your system. The release number information in the Registry report should match the 'member' release number information provided above for the software components installed on each machine in your deployment.

The hot fix downloaded, A5T020pt.zip, includes the updates required for all components listed above on all applicable operating systems. To apply this hot fix on multiple machines, you can either save A5T020pt.zip on each machine or save it in a network location that is accessible to all machines.

Do NOT extract the contents of A5T020pt.zip. The hot fix installation process will extract the contents as needed.

IMPORTANT NOTES

1. Files delivered in this hot fix will be backed up during the installation process. However, it is good general practice to back up your system before applying updates to software.
2. You must have Administrator Privileges on your CLIENT or SERVER machine.
3. All currently active SAS sessions must be terminated before applying this hot fix.
4. This hot fix should be installed using the same userid who performed the initial software installation.
5. CONFIGURATION: No automatic configuration scripting is included for this hot fix. If you have previously configured software installed, the SAS Deployment Manager may present a screen where you will see "Apply SAS Hot Fixes" and "Configure SAS Hot Fixes" options. On this screen, you must ensure that the "Configure SAS Hot Fix" option is ***not*** selected. If this option is automatically selected, please de-select it prior to proceeding with the SAS Deployment Manager Screens. Failure to do so could have unintended consequences when applying this hot fix.
6. For Oracle databases, the `NLS_LENGTH_SEMANTICS` setting may need to be set when creating the Compliance Solutions database tables. A setting of `CHAR` ensures that four bytes are allocated for each Unicode character in the column definitions. If this variable is not properly set, the number of bytes reserved for each column is too small and results in ORA-12899 (value too large for column) errors during program execution. The install and database administrator user may need to define the following environment variables prior to running the database scripts:

```
NLS_LANG=AMERICAN_AMERICA.AL32UTF8  
NLS_LENGTH_SEMANTICS=CHAR
```

INSTALLATION

Hot fix A5T020 must be installed on each machine where the updated components of the product, listed above, are installed. During the installation process you may see references to all operating systems for which updates are provided in the hot fix. The installation process will determine the operating system and which component(s) of Compliance Solutions 7.1 require updating on the machine. See [SAS Note 44810](#) for more details.

The hot fix will be applied using the SAS Deployment Manager. By default, the SAS Deployment Manager will search in the `<SASHOME>/InstallMisc/HotFixes/New` directory for hot fixes to be applied but will also prompt for a location if you have downloaded hot fixes to a different directory.

After downloading A5T020pt.zip, follow the instructions for applying hot fixes in the [SAS Deployment Wizard and SAS Deployment Manager 9.4: User's Guide](#).

Generally, it is not necessary to shut down any compute tier or metadata servers when executing the hotfix installation and post-installation steps for this hotfix. It is important, however, that SAS is not

executing on the compute tier server, because it can lock access to the Compliance Solutions compiled macros library, which cannot be in use when the library gets replaced with the new version. The SAS Deployment Manager will check for files in use by other processes and will issue an error if any are found.

Please review the CONFIGURATION Important Note above concerning proper selection of the "Configure SAS Hot Fix" option in the SAS Deployment Manager.

The hot fix installation process generates the log file:

```
<SASHOME>/InstallMisc/InstallLogs/IT_date-and-time-stamp.log
```

For example, IT_2011-10-31-13.18.21.log. Each attempt to apply a hot fix will result in the creation of a new log file giving detailed information regarding the installation process.

Postexec log files are created after the installation is completed and identifies the files that were added, backed up, changed, or removed. These log files include the 'member' hot fix id in the name of the file and are also written to the <SASHOME>/InstallMisc/InstallLogs directory. There is one postexec log for each 'member' hot fix applied (member hot fixes are listed at the top of these instructions).

Post-Installation Instructions:

NOTE: If you are installing out of the box, please ensure that you have completed the configuration of the base product prior to performing these Post-Installation Instructions.

Initial Notes

Important Note: For ease of completion of post-installation tasks, you can set the following environment variables:

UNIX:

This should be changed to the path where SAS was installed.

```
export SASHOME=/install/SASHome
```

This should be changed to the configuration folder and level for this deployment.

```
export SASCONFIG=/install/config/Lev1
```

This is the base folder where SAS Compliance Solutions and all business units are deployed.

```
export FCFBASE=${SASCONFIG}/Applications/SASComplianceSolutions
```

This will add the location of the SAS ant executable to the PATH.

```
export  
PATH=${SASHOME}/SASEnvironmentManagerAgent/2.5/installer/bin:${PATH}
```

WINDOWS:

This should be changed to the path where SAS was installed.

```
set SASHOME=C:\PROGRA~1\SASHOME
```

This should be changed to the configuration folder and level for this deployment.

```
set SASCONFIG=C:\SAS\Config\Lev1
```

This is the base folder where SAS Compliance Solutions and all business units are deployed.

```
set FCFBASE=C:\SAS\Config\Lev1\Applications\SASComplianceSolutions
```

This should add the location of ANT executable provided in the SAS installation, to the PATH.

```
set PATH=%SASHOME%\SASEnvironmentManagerAgent\2.5\installer\bin;%PATH%
```

Important Note about ant: if there is another, competing installation of **ant** on your system, it may not be suitable for the purposes of this procedure. It may use a version of **ant** that does not match the configuration code delivered with SAS, or it may not be configured to include the **ant-apache-regexp** package, which is needed for proper operation of these steps. If you have another installation of **ant** on your system, you need to temporarily remove it from the PATH and clear out the value of the ANT_HOME environment variable, so that the version installed with SAS will be used.

Important Note: hotfix 16 (A5R018) comprises all compute tier changes made for hotfix 1 (A5R001), hotfix 2 (A5R003), hotfix 3 (A5R004), hotfix 4 (A5R005), hotfix 5 (A5R006), hotfix 6 (A5R007), hotfix 7 (A5R009), hotfix 8 (A5R010), hotfix 9 (A5R011), hotfix 10 (A5R012), hotfix 10icf1 (A5R013), hotfix 11 (A5R014), hotfix 12 (A5R015), hotfix 13 (A5R016), hotfix 14 (A5R016), and hotfix 15 (A5R017), as well as new changes made for hotfix 16 (A5R018). Reinstalling a hotfix could result in errors and lost data so ensure you choose the correct command in the Hotfix-Configuration Steps based on your existing hotfix level installed.

Important Note: hotfix 15 (A5R019) replaces log4j v1 with log4j v2 and will replace the contents of the config/Lev1/Web/Common/LogConfig/SASComplianceSolutionsMid-log4j.xml file. If you have modified this file you should back up the file and then apply the changes using the log4j v2 configuration parameters as documented here: <https://logging.apache.org/log4j/log4j-2.7/manual/migration.html>.

Important Note: hotfix 2 (A5R003), hotfix 3 (A5R004), and hotfix 16 (A5R018) will replace the contents of FSK_LOV and reset the mid-tier application server preferences to default values.

Database Changes by Hotfix

Hotfix 1 Database Changes

Hotfix 1 (HF1) delivers Customer Due Diligence for the first time. It contains data model changes that, when executed, will drop the tables listed below. Do not execute HF1 database steps if HF1 has already been installed. All data in the tables will be deleted, and the tables will be created again with new table definitions. This is a destructive process and if these tables contain data from previous releases of CDD, your data should be backed up before these steps are executed.

The following tables will be dropped when the DDL is executed:

```
FCFKC.FSK_CDD_RULE  
FCFKC.FSK_CDD_RULE_PARAMETER
```

```
FCFKC.FSK_CDD_RULE_GROUP
FCFKC.FSK_CDD_SCORING_EVENT
```

The following tables will be created when the DDL is executed:

```
FCFKC.FSK_CDD_REVIEW
FCFKC.FSK_CDD_REVIEW_EVENT
FCFKC.FSK_CDD_EDD_REVIEW
```

The following table will be altered:

```
FCFKC.FSK_RC_FORM_CONFIG
```

Hotfix 2 Database Changes

Hotfix 2 (HF2) only alters existing tables, so no data model changes will result in data loss. The following tables will be altered:

```
FCFKC.FSK_RC_REPORT
FCFKC.FSK_CASE
```

Hotfix 3 Database Changes

Hotfix 3 (HF3) only alters existing tables, so no data model changes will result in data loss. The following table will be altered:

```
FCFKC.FSK_RC_REPORT_ENTITY_INFO
```

Hotfix 4 Database Changes

Hotfix 4 (HF4) delivers several data model changes. The data model changes, when executed, will drop the tables listed below. **This will result in data loss** that can be restored by baking up the data and restoring it according to the instructions below.

Hotfix 4 will delete all data in the following tables, then it will create the tables again with new table definitions. This is a destructive process and there will be a loss of data that will affect the Alert Triage UI. The tables will be repopulated when the Alert Generation Process (AGP) is executed with HF4 applied.

The following tables will be dropped and recreated:

```
FCFKC.FSK_ALERTED_ENTITY
FCFKC.FSK_ALERT_TRANSACTION
FCFKC.FSK_ENTITY_TRANSACTION
FCFKC.FSK_ENTITY_TX_AGG
FCFKC.FSK_ALERT_TX_AGG
```

The Hotfix 4 (HF4) data model changes replace the `ALERTED_ENTITY_KEY` with the `ALERTED_ENTITY_NUMBER` in the Alert Triage Datamart. The Alert Triage Datamart tables contain no historical data except owner assignment for alerted entities (see steps below describing the procedure to save owner assignment information). The tables are rebuilt at the end of each run of the AGP. It is possible to load the Alert Triage Datamart prior to the next execution of the AGP, if you

execute the macro %fcf_ent_load_dm_process. Prior to executing this macro, the fcf_autoexec.sas script must be executed, the macro %fcf_start_datetime_init must be executed, the macro %fcf_start_datetime_read must be executed, and the &runasofdate macro variable must be set. The datamart macros in HF4 are also dependent on the changes to the FSC_EXT_PARTY_ACCOUNT_DIM table described below.

The following table will be altered:

```
FCFKC.FSC_EXT_PARTY_ACCOUNT_DIM
```

Hotfix 4 introduces a change to the FSC_EXT_PARTY_ACCOUNT_DIM table. This table has been changed to be a *Slowly Changing Dimensions Type 2* (SCD2) table. This is done to ensure that external party alerts are displayed and triaged correctly in the investigation UI.

Hotfix 5 Database Changes

Hotfix 5 (HF5) delivers several data model changes. It creates new tables:

```
FCFKC.FSK_SEGMENT  
FCFKC.FSK_QUEUE  
FCFKC.FSK_ENTITY_QUEUE  
FCFKC.FSK_RC_REPORT_ENTITY_BRIDGE
```

and alters several existing tables with no data loss:

```
FCFCORE.FSC_ACCOUNT_DIM  
FCFCORE.FSC_PARTY_DIM  
FCFKC.FSK_ALERT  
FCFKC.FSK_SCENARIO  
FCFKC.FSK_SCENARIO_PARAMETER  
FCFKC.FSK_ALERTED_ENTITY  
FCFKC.FSK_CASE  
FCFKC.FSK_CDD_REVIEW  
FCFKC.FSK_RC_REPORT
```

For **Teradata databases** the FCFKC.FSK_SCENARIO_PARAMETER table that will be altered has to be empty to create a new primary index, so the content of this table must be saved and then restored.

For **Microsoft SQL Server databases** there is now an optional manual process to convert all fields that could contain multi-byte characters to NVARCHAR. The process for doing this is documented in the Optional Configuration Steps further down this document.

NOTE: The ENTITY_SEGMENT_ID field was added into the FSK_SEGMENT, FSC_ACCOUNT_DIM, FSC_PARTY_DIM, FSK_ALERT, and FSK_SCENARIO_PARAMETER tables. The field ALERTED_ENTITY_SEGMENT_ID was added to the FSK_ALERTED_ENTITY table. These fields were introduced because of the new scenario segmentation feature. AGP may fail if you execute custom scenario headers after applying hotfix 5. See [SAS Note 63357](#) for more information.

Hotfix 6 Database Changes

Hotfix 6 will delete all data in the following Funds Tracker table, then it will recreate the table with new table definitions. This table will be repopulated when `fcf_fundstracker_create_data.sas` is executed.

The following table will be dropped and recreated:

```
FCFKC.FSK_INT_XFER
```

Hotfix 7 Database Changes

Hotfix 7 (HF7) delivers several data model changes. It creates a new table:

```
FCFKC.FSK_RC_EFILE_EVENT
```

and alters several existing tables with no data loss:

```
FCFCORE.FSC_PARTY_DIM  
FCFKC.FSK_PREFERENCE  
FCFKC.FSK_ALERTED_ENTITY  
FCFKC.FSK_RC_REPORT  
FCFKC.FSK_CDD_REVIEW  
FCFKC.FSK_RC_EFILE  
FCFKC.FSK_CASE
```

Hotfix 8 Database Changes

Hotfix 8 (HF8) does not contain any updates to the data model.

Hotfix 9 Database Changes

Hotfix 9 (HF9) does not contain any updates to the data model.

Hotfix 10 Database Changes

Hotfix 10 (HF10) does not contain any updates to the data model.

Hotfix 10_ICF1 Database Changes

Hotfix 10_ICF1 (HF10icf1) does not contain any updates to the data model.

Hotfix 11 Database Changes

Hotfix 11 (HF11) does not contain any updates to the data model.

Hotfix 12 Database Changes

Hotfix 12 (HF12) does not contain any updates to the data model.

Hotfix 13 Database Changes

Hotfix 13 (HF13) does not contain any updates to the data model.

Hotfix 14 Database Changes

Hotfix 14 (HF14) does not contain any updates to the data model.

Hotfix 15 Database Changes

Hotfix 15 (HF15) does not contain any updates to the data model.

Hotfix 16 Database Changes

Hotfix 16 (HF16) does not contain any updates to the data model.

Capabilities Changes by Hotfix and Role

See the [What's New in SAS Anti-Money Laundering 7.1](#) document for information about changes to the capabilities in each Hotfix.

Hotfix-Configuration Process: Execute for each Business Unit

The **hotfix (A5R018)** contains changed files that need to be applied to every business unit that is configured; for example: FCFBU1, FCFBU2, and FCFBU3. The following Pre-Hotfix-Configuration Steps, Hotfix-Configuration Steps, and Post-Configuration Steps must be repeated for each business unit, substituting the business unit name wherever you see 'FCFBU1' in the steps below. Execute these steps for the first business unit, then execute the steps for the second business unit. Repeat as necessary until all business units have been configured.

NOTE: When a new business unit is created, it is created at the base level and all hotfixes should be applied even if other business units have already been created and updated to later hot fix levels.

Pre-Hotfix-Configuration Steps

1. It is vitally important that you back up your business unit databases.
2. It is vitally important that you back up your business unit folder before you proceed with the next step.

For UNIX, back up

```
$SASCONFIG/Applications/SASComplianceSolutions/FCFBU1
```

with its subdirectories.

For Windows, back up

```
%SASCONFIG%\Applications\SASComplianceSolutions\FCFBU1
```

with its subdirectories.

Repeat this backup procedure for each business unit in the system.

3. **For hotfix 5 (A5R006):** If there is no need to preserve owner assignment for alerted entities then skip this step, the Alert Triage Datamart tables are rebuilt at the end of each run of the AGP or they can be populated by running the `%fcf_ent_load_dm_process` macro as described in one of the steps below.

To save owner assignment for alerted entities, back up the content of the

FSK_ALERTED_ENTITY table before executing the script in the next step and then restore the table content using the backed-up table as the source.

There are many ways that the content of the table can be backed up, below is an example using SAS code, please consult your DBA for the appropriate solution for your specific deployment:

```
%inc
"/install/config/Lev1/Applications/SASComplianceSolutions/FCFBU1/custom
/config/aml_autoexec.sas";

/* Step 1 - save the data - execute before HF5
changes */

data cmddata.FSK_ALERTED_ENTITY_SAVE;
  set seg_kc.FSK_ALERTED_ENTITY;
run;

/* Step 2 - restore data - execute after applying HF5 changes
*/
PROC SQL;

insert into seg_kc.FSK_ENTITY_QUEUE (
  QUEUE_CODE, ALERTED_ENTITY_LEVEL_CODE,
  ALERTED_ENTITY_NUMBER, OWNER_USERID)
select
  '' as QUEUE_CODE,
  ALERTED_ENTITY_LEVEL_CODE,
  ALERTED_ENTITY_NUMBER,
  owner_userid
QUIT;

from cmddata.FSK_ALERTED_ENTITY_SAVE;
```

After the content of the table is restored, it is safe to run AGP or the

%fcf_ent_load_dm_process macro, the owner assignment will be preserved.

4. **hotfix 5 (A5R006): For Teradata databases only** (skip this step for other databases):

Backup the content of the FCFKC.FSK_SCENARIO_PARAMETER table before executing the HF5 deployment script in the next step. The script will execute a hotfix 5 DDL script that is going to modify the unique primary index on the FCFKC.FSK_SCENARIO_PARAMETER table and Teradata requires the table to be empty. When next step is complete restore the content of the FCFKC.FSK_SCENARIO_PARAMETER table populating new column ENTITY_SEGMENT_ID with value -1. There are many ways that the content of the table can be backed up, below is an example using SAS code, please consult your DBA for the appropriate solution for your specific deployment:

```
%inc
"/install/config/Lev1/Applications/SASComplianceSolutions/FCFBU1/custom/conf
ig/aml_autoexec.sas";
```

```

libname terakc teradata user=XXX password=xxx server=teradata1234
schema=fcfkc MULTISTMT=YES;

/* Step 1 - save the data - execute before applying HF5 changes */

data cmndata.FSK_SCENARIO_PARAMETER_SAVE;
set terakc.FSK_SCENARIO_PARAMETER; LENGTH entity_segment_id 8.;
entity_segment_id = -1;
run;

/* Step 2 - restore data - execute after applying HF5 changes */

PROC APPEND BASE=terakc.FSK_SCENARIO_PARAMETER
DATA=cmndata.FSK_SCENARIO_PARAMETER_SAVE;
RUN;

```

5. The metadata server must be running. To start the metadata server, execute:

```

$SASCONFIG/SASMeta/MetadataServer/MetadataServer.sh start

```

6. Change the current directory to the \$FCFBASE/**FCFBU1**/config folder.

The Ant build.xml file has been updated in the hotfix release, so you need to copy the new version into your configuration folder:

for UNIX:

```

cp $SASHOME/SASFoundation/9.4/misc/antimnycmn/deploy/script/build.xml .

```

for Windows:

```

copy
%SASHOME%\SASFoundation\9.4\antimnycmn\sasmisc\deploy\script\build.xml .

```

There should already exist a file named **build.properties** in the current folder, that was used when configuring the system. The file might have been deleted after the business unit was initially configured if sensitive login passwords needed to be protected. If that is the case, the **build.properties** file needs to be created according to the instructions provided in the SAS Anti-Money Laundering 7.1 Installation and Configuration Guide, Chapter 5, Post-Configuration, in the section titled "Configure Compute Tier Business Units."

There should already exist a file named **deployment.properties** in the current folder, that was used when configuring the system. The file might have been deleted after the business unit was initially configured if sensitive login passwords needed to be protected. If that is the case, the **deployment.properties** file should be copied from \$SASCONFIG/Applications/SASComplianceSolutions/deployment.properties to the current folder before executing this script.

You will need to provide a value for the following property:

```

jdbc.driver.dir=/install/jdbc/oracle

```

You should not specify the name of the driver in this variable, just the path; the driver name will be appended automatically depending on the DBMS selected.

To connect to the metadata server, you need to provide a value for the following properties:

```
metadata.user=sasadm@saspw
metadata.password=password
```

To connect to the DBMS and execute the Database DDL, you need to provide a value for the `system` account:

```
dbms.system.userid=system
dbms.system.passwd=password
```

7. **Upgrade to Apache Solr 8.6.2 for hotfix 16 (A5R018):** If Apache Solr 5.5.5 is installed on your system, it must be upgraded to Apache Solr 8.6.2 for this release. The install procedure is described in the latest version of the SAS Anti-Money Laundering Installation and Configuration Guide, under the *Prerequisites* section, *Pre-Installation Tasks* subsection, under the heading Install Apache Solr 8.6.2. If you are using Zookeeper, you may also download and install Zookeeper 3.5.7.

After Solr 8.6.2 has been installed, for each business unit on the compute tier server you need to change the `$FCFBASE/FCFBUL/config/build.properties` file to point to the installation location of the new Solr version. Change the following setting:

```
solr.dir=/install/solr.8.6.2
```

You will need to stop the existing Solr 5.5.5 server using the following command:

```
/install/solr-5.5.5/bin/solr stop -all
```

Next you will configure the Solr server for each business unit by changing to the `$FCFBASE/<business unit id>/config` folder and executing the Ant configuration script with the following parameters:

```
ant solr_standalone -logfile hotfix16_solr_standalone.log
```

After the Solr 8.6.2 server is configured, you will need to re-index the Solr documents. To accomplish this, consult the **SAS Anti-Money Laundering Installation and Configuration Guide**, under the *Post-Configuration* section, in the *Configuring Apache Solr* subsection under the heading *Import Data into Apache Solr*.

Hotfix-Configuration Steps

NOTE: this section has been reworked from previous hotfixes so that you do not need to run commands for all hotfix levels being configured. The command(s) that are run with this hotfix are based on the latest hotfix level that has been applied to this business unit. For example, if you do not have any hotfixes applied to this business unit then you will run the command associated with the **Base system – no hotfixes applied** row. If you have hotfix 4 applied to this business unit then you will run the command associated with the **Hotfix 4 applied** row.

In this section, you will be running an ant script that uses the `build.xml` file you copied in step 6 above. Choose the section below, *Have Authority to run DB DDL* or *Do Not Have Authority to run DB DDL*,

based on whether your site requires the DBA to run the Database DDL scripts to update the database. If you do not have the authority to run the Database DDL scripts to update the database, skip to the *Do Not Have Authority to run DB DDL* section below.

Have Authority to run DB DDL

This section is for those who have the authority to run the Database DDL scripts to update the database and have entered values for the `dbms.system.userid` and `dbms.system.passwd` in the `build.properties` file.

1. This step will configure and run all the Database DDL required based on the current level of hotfix applied to this business unit. Run the command to configure the hotfix based on the current level of hotfix installed on the Business Unit.

NOTE: Newly created business units are at the base system level and require all hotfixes to be applied.

Latest hotfix applied to this Business Unit	Command to run to configure the hotfix from the \$FCFBASE/FCFBU1/config folder
Base system – no hotfixes applied	ant hotfix_from_base -logfile hotfix_from_base.log
Hotfix 1 applied	ant hotfix_from_hotfix1 -logfile hotfix_from_hotfix1.log
Hotfix 2 applied	ant hotfix_from_hotfix2 -logfile hotfix_from_hotfix2.log
Hotfix 3 applied	ant hotfix_from_hotfix3 -logfile hotfix_from_hotfix3.log
Hotfix 4 applied	ant hotfix_from_hotfix4 -logfile hotfix_from_hotfix4.log
Hotfix 5 applied	ant hotfix_from_hotfix5 -logfile hotfix_from_hotfix5.log
Hotfix 6 applied	ant hotfix_from_hotfix6 -logfile hotfix_from_hotfix6.log
Hotfix 7 applied	ant hotfix_from_hotfix7 -logfile hotfix_from_hotfix7.log
Hotfix 8 applied	ant hotfix_from_hotfix8 -logfile hotfix_from_hotfix8.log
Hotfix 9 applied	ant hotfix_from_hotfix9 -logfile hotfix_from_hotfix9.log
Hotfix 10 applied	ant hotfix_from_hotfix10 -logfile hotfix_from_hotfix10.log
Hotfix 10icf1 applied	ant hotfix_from_hotfix10icf1 -logfile hotfix_from_hotfix10icf1.log
Hotfix 11 or Hotfix 11icf1 applied	ant hotfix_from_hotfix11 -logfile hotfix_from_hotfix11.log
Hotfix 12 applied	ant hotfix_from_hotfix12 -logfile hotfix_from_hotfix12.log
Hotfix 13 applied	ant hotfix_from_hotfix13 -logfile hotfix_from_hotfix13.log

Hotfix 14 applied	ant hotfix_from_hotfix14 -logfile hotfix_from_hotfix14.log
Hotfix 15 applied	ant hotfix_from_hotfix15 -logfile hotfix_from_hotfix15.log

2. After running the command, check the log file to ensure there are no errors.

3. **hotfix 5 (A5R006):** For Microsoft SQL Server installations, log into your local SQL Server database and run the following DDL commands to recreate the FSK_SCENARIO_PARAMETER view. Substitute your business unit name for **FCFBU1**.

```
ALTER VIEW FCFBU1.FSK_SCENARIO_PARAMETER AS SELECT * FROM
FCFKC.FSK_SCENARIO_PARAMETER

GO
```

4. Skip to the Post-Hotfix-Configuration Steps section below.

Do Not Have Authority to run DB DDL

This section is for those who do not have the authority to run the Database DDL scripts to update the database and need to provide scripts to the DBA for update. Steps 1 and 5 do not require DBA authority.

1. This step will configure and prepare the Database DDL that you will provide to the DBA based on the current level of hotfix applied to this business unit. Run the command to configure the Database DDL based on the current level of hotfix installed on the Business Unit.

Latest hotfix applied to this Business Unit	Command to run to configure the Database DDL from the \$FCFBASE/FCFBU1/config folder
Base system – no hotfixes applied	ant pre_db_from_base -logfile pre_db_from_base.log
Hotfix 1 applied	ant pre_db_from_hotfix1 -logfile pre_db_from_hotfix1.log
Hotfix 2 applied	ant pre_db_from_hotfix2 -logfile pre_db_from_hotfix2.log
Hotfix 3 applied	ant pre_db_from_hotfix3 -logfile pre_db_from_hotfix3.log
Hotfix 4 applied	ant pre_db_from_hotfix4 -logfile pre_db_from_hotfix4.log
Hotfix 5 applied	ant pre_db_from_hotfix5 -logfile pre_db_from_hotfix5.log
Hotfix 6 applied	ant pre_db_from_hotfix6 -logfile pre_db_from_hotfix6.log
Hotfix 7 applied	ant pre_db_from_hotfix7 -logfile pre_db_from_hotfix7.log
Hotfix 8 applied	ant pre_db_from_hotfix8 -logfile pre_db_from_hotfix8.log

Hotfix 9 applied	ant pre_db_from_hotfix9 -logfile pre_db_from_hotfix9.log
Hotfix 10 applied	ant pre_db_from_hotfix10 -logfile pre_db_from_hotfix10.log
Hotfix 10icf1 applied	ant pre_db_from_hotfix10icf1 -logfile pre_db_from_hotfix10icf1.log
Hotfix 11 or Hotfix 11icf1 applied	ant pre_db_from_hotfix11 -logfile pre_db_from_hotfix11.log
Hotfix 12 applied	ant pre_db_from_hotfix12 -logfile pre_db_from_hotfix12.log
Hotfix 13 applied	ant pre_db_from_hotfix13 -logfile pre_db_from_hotfix13.log
Hotfix 14 applied	ant pre_db_from_hotfix14 -logfile pre_db_from_hotfix14.log
Hotfix 15 applied	ant pre_db_from_hotfix15 -logfile pre_db_from_hotfix15.log

2. After running the command, check the log file to ensure there are no errors.
3. Provide the following Database DDL scripts to your DBA for database updates. Replace the xxx with **db2**, **oracle**, **sqlserver**, or **teradata** based on your version of dbms. These Database DDL scripts need to be run in the specified order.

Latest hotfix applied to this Business Unit	Files located in the \$FCFBASE/FCFBU1/ddl folder to provide to DBA for database updates
Base system – no hotfixes applied	xxx_7.1_all_hotfixes_ddl.sql
Hotfix 1 applied	xxx_7.1_to_7.1HF2_ddl.sql xxx_7.1_to_7.1HF3_ddl.sql xxx_7.1_to_7.1HF4_ddl.sql xxx_7.1_to_7.1HF5_ddl.sql xxx_7.1_to_7.1HF6_ddl.sql xxx_7.1_to_7.1HF7_ddl.sql
Hotfix 2 applied	xxx_7.1_to_7.1HF3_ddl.sql xxx_7.1_to_7.1HF4_ddl.sql xxx_7.1_to_7.1HF5_ddl.sql xxx_7.1_to_7.1HF6_ddl.sql xxx_7.1_to_7.1HF7_ddl.sql
Hotfix 3 applied	xxx_7.1_to_7.1HF4_ddl.sql xxx_7.1_to_7.1HF5_ddl.sql xxx_7.1_to_7.1HF6_ddl.sql xxx_7.1_to_7.1HF7_ddl.sql

Hotfix 4 applied	xxx_7.1_to_7.1HF5_ddl.sql xxx_7.1_to_7.1HF6_ddl.sql xxx_7.1_to_7.1HF7_ddl.sql
Hotfix 5 applied	xxx_7.1_to_7.1HF6_ddl.sql xxx_7.1_to_7.1HF7_ddl.sql
Hotfix 6 applied	xxx_7.1_to_7.1HF7_ddl.sql
Hotfix 7 applied	<i>No updates required</i>
Hotfix 8 applied	<i>No updates required</i>
Hotfix 9 applied	<i>No updates required</i>
Hotfix 10 applied	<i>No updates required</i>
Hotfix 10icf1 applied	<i>No updates required</i>

Hotfix 11 or Hotfix 11icf1 applied	<i>No updates required</i>
Hotfix 12 applied	<i>No updates required</i>
Hotfix 13 applied	<i>No updates required</i>
Hotfix 14 applied	<i>No updates required</i>
Hotfix 15 applied	<i>No updates required</i>

4. After the DBA runs the Database DDL, complete the configuration of the hotfix by running the following command based on the current hotfix level applied to this business unit.

Latest hotfix applied to this Business Unit	Command to run to apply the hotfix(es) from the \$FCFBASE/FCFBU1/config folder
Base system – no hotfixes applied	ant post_db_from_base -logfile post_db_from_base.log
Hotfix 1 applied	ant post_db_from_hotfix1 -logfile post_db_from_hotfix1.log
Hotfix 2 applied	ant post_db_from_hotfix2 -logfile post_db_from_hotfix2.log
Hotfix 3 applied	ant post_db_from_hotfix3 -logfile post_db_from_hotfix3.log
Hotfix 4 applied	ant post_db_from_hotfix4 -logfile post_db_from_hotfix4.log

Hotfix 5 applied	ant post_db_from_hotfix5 -logfile post_db_from_hotfix5.log
Hotfix 6 applied	ant post_db_from_hotfix6 -logfile post_db_from_hotfix6.log
Hotfix 7 applied	ant post_db_from_hotfix7 -logfile post_db_from_hotfix7.log
Hotfix 8 applied	ant post_db_from_hotfix8 -logfile post_db_from_hotfix8.log
Hotfix 9 applied	ant post_db_from_hotfix9 -logfile post_db_from_hotfix9.log
Hotfix 10 applied	ant post_db_from_hotfix10 -logfile post_db_from_hotfix10.log
Hotfix 10icf1 applied	ant post_db_from_hotfix10icf1 -logfile post_db_from_hotfix10icf1.log
Hotfix 11 or Hotfix 11icf1 applied	ant post_db_from_hotfix11 -logfile post_db_from_hotfix11.log
Hotfix 12 applied	ant post_db_from_hotfix12 -logfile post_db_from_hotfix12.log
Hotfix 13 applied	ant post_db_from_hotfix13 -logfile post_db_from_hotfix13.log
Hotfix 14 applied	ant post_db_from_hotfix14 -logfile post_db_from_hotfix14.log
Hotfix 15 applied	ant post_db_from_hotfix15 -logfile post_db_from_hotfix15.log

- After running the command, check the log file to ensure there are no errors.
- hotfix 5 (A5R006):** For Microsoft SQL Server installations, log into your local SQL Server database and run the following DDL commands to recreate the FSK_SCENARIO_PARAMETER view. Substitute your business unit name for **FCFBU1**.

```
ALTER VIEW FCFBU1.FSK_SCENARIO_PARAMETER AS
SELECT * FROM FCFKC.FSK_SCENARIO_PARAMETER

GO
```

Post-Hotfix-Configuration Steps

- hotfix 5 (A5R006):** If you backed up the contents of the FSK_ALERTED_ENTITY table, restore the data. If there is no need to preserve owner assignment for alerted entities then skip this step, the Alert Triage Datamart tables are rebuilt at the end of each run of the AGP or they can be populated by running the %fcf_ent_load_dm_process macro as described in one of the steps below.

To save owner assignment for alerted entities, back up the content of the FSK_ALERTED_ENTITY table before executing the script in the next step and then restore the table content using the backed-up table as the source.

There are many ways that the content of the table can be backed up, below is an example using SAS code, please consult your DBA for the appropriate solution for your specific deployment:

```

%inc "/install/config/Levl/Applications/SASComplianceSolutions/FCFBU1/custom/
config/aml_autoexec.sas";

/* Step 1 - save the data - execute before HF5 changes */
data cmndata.FSK_ALERTED_ENTITY_SAVE;
  set seg_kc.FSK_ALERTED_ENTITY;
run;

/* Step 2 - restore data - execute after applying HF5 changes */
PROC SQL;
  insert into seg_kc.FSK_ENTITY_QUEUE (
    QUEUE_CODE,
    ALERTED_ENTITY_LEVEL_CODE,
    ALERTED_ENTITY_NUMBER,
    OWNER_USERID)
  select
    '' as QUEUE_CODE,
    ALERTED_ENTITY_LEVEL_CODE,
    ALERTED_ENTITY_NUMBER,
    owner_userid
  from cmndata.FSK_ALERTED_ENTITY_SAVE;
QUIT;

```

After the content of the table is restored, it is safe to run AGP or the %fcf_ent_load_dm_process macro, the owner assignment will be preserved.

2. **hotfix 5 (A5R006):** For **Teradata databases only** (skip this step for other databases):

Restore the content of the FCFKC.FSK_SCENARIO_PARAMETER table populating new column ENTITY_SEGMENT_ID with value -1. There are many ways that the content of the table can be backed up, below is an example using SAS code, please consult your DBA for the appropriate solution for your specific deployment:

```

%inc "/install/config/Levl/Applications/SASComplianceSolutions/FCFBU1/cust
om/config/aml_autoexec.sas";

libname terakc teradata user=XXX password=xxx server=teradata1234
schema=fcfkc MULTISTMT=YES;

/* Step 1 - save the data - execute before applying HF5 changes */
data cmndata.FSK_SCENARIO_PARAMETER_SAVE;
  set terakc.FSK_SCENARIO_PARAMETER;
  LENGTH entity_segment_id 8.;
  entity_segment_id = -1;
run;

/* Step 2 - restore data - execute after applying HF5 changes */
PROC APPEND
  BASE=terakc.FSK_SCENARIO_PARAMETER
  DATA=cmndata.FSK_SCENARIO_PARAMETER_SAVE;
RUN;

```

3. Start the compute tier servers:

```
 ${SASCONFIG}/sas.servers start
```

- Restart the SOLR server after all business units have had the hotfix applied. For UNIX, execute:

```
 ${SOLR_HOME}/bin/solr restart
```

- For Windows, execute:

```
 %SOLR_HOME%\bin\solr.cmd restart -port 8983
```

- Rebuild the SOLR indexes for the updated entities. Navigate to the Solr Administration console by entering the following URL into your browser:

http://compute_tier_server:8983/solr/#/CS-FCFBU1/dataimport//import/aml/entities

Next, set **Command** to **full-import** and uncheck the **Clean** checkbox and check the **Commit** checkbox. To index a specific entity, select the entity listed in the table below based on the current level of hotfix installed. Check the **Auto-Refresh Status** box if you want to monitor task progress and press the Execute button.

Latest hotfix applied to this Business Unit	Entities which need to be reindexed
Base system – no hotfixes applied	ewatchlist case ext alert customer
Hotfix 1 applied	ewatchlist case ext alert customer
Hotfix 2 applied	ewatchlist case ext alert customer
Hotfix 3 applied	ewatchlist case ext alert customer
Hotfix 4 applied	case ext alert customer
Hotfix 5 applied	alert customer
Hotfix 6 applied	alert customer

Hotfix 7 applied	alert customer
Hotfix 8 applied	alert customer
Hotfix 9 applied	alert customer
Hotfix 10 applied	alert
Hotfix 10icf1 applied	alert
Hotfix 11 or Hotfix 11icf1 applied	No reindexing is required
Hotfix 12 applied	No reindexing is required
Hotfix 13 applied	No reindexing is required
Hotfix 14 applied	No reindexing is required
Hotfix 15 applied	alert account associate bank branch case cddreview customer ext hhd report risk

Repeat this step until all the entities required have been reindexed. For example, if hotfix 11 is being applied to a system with hotfix 4 already installed then the **case, ext, alert** and **customer** entities should be reindexed. If hotfix 11 is being applied to a system with hotfix 3 already installed then the **ewatchlist, case, ext, alert** and **customer** entities should be reindexed.

7. **hotfix 5 (A5R006)** Review the sample program:

`$FCFBASE/FCFBU1/regulatoryConsole/rc_template/rc_fincen_load_sample_data.sas`

Decide if you need to re-execute the program, since the sample data has changed in the hotfix delivery.

Follow the instructions under "Institution and Branch Setup for FinCEN Forms" in Chapter 6, "Regulatory Reports and E-Filing" from the [SAS Anti-Money Laundering 7.1: Administration Guide](#).

8. **hotfix 4 (A5R005):** When the hotfix 4 deployment script was executed it added three additional columns to the `FSC_EXT_PARTY_ACCOUNT_DIM` table with default values. You need to ensure that the table contains correct data for the AGP and UI to use and that it is also SCD2 compliant. To accomplish this, a couple of additional steps are required:

- a. The ETL process needs to be modified to make sure that entity resolution is performed for external parties and the FSC_EXT_PARTY_ACCOUNT_DIM table is updated correctly. The AGP and UI code assumes that EXTERNAL_PARTY_NUMBER column values are unique for each party and all the records with the same value in EXTERNAL_PARTY_NUMBER are for the same party and only one record for each party has CHANGE_CURRENT_IND = 'Y'. All UI and AGP queries will use the record with CHANGE_CURRENT_IND = 'Y' as the current record for the party.
- b. Review your data in the FSC_EXT_PARTY_ACCOUNT_DIM table and make sure that there is only one record with CHANGE_CURRENT_IND = 'Y' for each party number in EXTERNAL_PARTY_NUMBER. For example, execute the query below:

```
select count(*) as DUP_COUNT, EXTERNAL_PARTY_NUMBER from
FCFCORE.FSC_EXT_PARTY_ACCOUNT_DIM
where CHANGE_CURRENT_IND='Y'
group by EXTERNAL_PARTY_NUMBER;
```

Analyze and fix records where DUP_COUNT > 1. Because EXTERNAL_PARTY_NUMBER is used as a foreign key for the FSC_CASH_FLOW_FACT table, such records cannot be simply deleted without deleting the transactions first. The easiest workaround is to set CHANGE_CURRENT_IND='N' for all records but one, for example one where EXT_PARTY_ACCOUNT_KEY has the max value.

Oracle workaround example:

```
update
FCFCORE.FSC_EXT_PARTY_ACCOUNT_DIM e
set
CHANGE_CURRENT_IND = 'N',
CHANGE_BEGIN_DATE = CREATE_DTTM,
CHANGE_END_DATE = CURRENT_DATE
where
CHANGE_CURRENT_IND='Y' and
exists
( select *
from FCFCORE.FSC_EXT_PARTY_ACCOUNT_DIM e1
where
e1.CHANGE_CURRENT_IND='Y' and
e.EXT_PARTY_ACCOUNT_KEY < e1.EXT_PARTY_ACCOUNT_KEY and
e.EXTERNAL_PARTY_NUMBER = e1.EXTERNAL_PARTY_NUMBER
);
```

This change does not guarantee that the data will be valid because entity resolution was not performed but it will make the data SCD2 compliant for AGP and UI queries. Completing step #1 above ensures that all the future data in the table will be valid.

As an alternative to the workaround described above, you can back up the FSC_CASH_FLOW_BANK_BRIDGE, FSC_CASH_FLOW_FACT and FSC_EXT_PARTY_ACCOUNT_DIM tables, delete all the records from FSC_CASH_FLOW_BANK_BRIDGE and from FSC_CASH_FLOW_FACT. Then perform proper entity resolution on FSC_EXT_PARTY_ACCOUNT_DIM and fix the EXTERNAL_PARTY_NUMBER values if necessary, by making them unique for each party. Re-populate FSC_CASH_FLOW_FACT and FSC_CASH_FLOW_BANK_BRIDGE using new party keys if necessary.

9. If you wish to reload the Alert Triage Datamart prior to the next execution of the AGP, you must use SAS to execute the macro %fcf_ent_load_dm_process as part of a SAS program like the following:

```
%include
"<SASCONFIG>/Applications/SASComplianceSolutions/
FCFBU1/custom/config/fcf_autoexec.sas";

%fcf_get_runasofdate
%fcf_start_datetime_init
%fcf_start_datetime_read
%fcf_ent_load_dm_process
```

If you choose not to reload the datamart tables, they will be reloaded during the next AGP execution. The SAS Compliance Solutions web application will not display information correctly until the datamart is updated.

10. For security reasons, you should modify your **build.properties** file to erase any clear text passwords stored in the file.
11. For FinCEN Regulatory Report implementations, the 'Validate Report' functionality for XML-based reports will require the 'Allow XCMD' option for the SAS Stored Process Server. Refer to the [SAS Anti-Money Laundering 7.1: Administration Guide](#) for instructions in the "FinCEN Report Implementation Post-Installation Steps" on enabling this capability. Also, if 'Validate Report' produces the error "Unable to locate Java executable passed with java_loc option.", the JAVA_HOME environment variable was not defined to locate the java executable. To resolve the issue, define the JAVA_HOME environment variable for SAS sessions, or modify the rc_validate_xml_driver.sas macro, and provide the java_loc option when invoking the %rc_validate_xml macro. For example:

```
%rc_validate_xml(
xml_file=&fullpathnm.,
xsd_file=&rc_template_path.&slash.schema&slash.FINCEN&slash.%lowc
ase(&form_type_code.)
_schema.xsd,,
error_file=&error_file.,
```



```
java_loc=c:\install\SASHome\SASPrivateJavaRuntimeEnvironment\9.4\
jre\bin\java.exe);
```

For any additional business units, you must repeat all these steps for each business unit.

Optional Configuration Steps

Microsoft SQL Server: Convert to nvarchar

NOTE: Please read [SAS Note 63032](#) prior to performing the nvarchar conversion.

To convert the Data Model stored in Microsoft SQL Server to use the NVARCHAR data type.

execute the following command from the \$FCFROOT/**FCFBU1**/config directory:

```
ant convert_to_nvarchar -logfile convert_to_nvarchar.log
```

After the command is finished, check the log file for errors. If you have installed and configured Hotfix 6 prior to doing the conversion to nvarchar then you will receive warnings in the log file for the two columns in the FCFKC.FSK_INT_XFER table.

This concludes the compute tier portion of the hotfix configuration.

A5Q019 Updates SAS Compliance Solutions Mid-Tier 7.1

Important Note: For ease of completion of post-installation tasks, you can set the following environment variables:

UNIX:

```
# This should be changed to the path where SAS was installed.
export SASHOME=/install/SASHome
```

```
# This should be changed to the configuration folder and level for this deployment.
export SASCONFIG=/install/config/Lev1
```

```
# This is the base folder where SAS Compliance Solutions and all business units are deployed.
export FCFBASE=${SASCONFIG}/Applications/SASComplianceSolutions
```

```
# This will add the location of the SAS ant executable to the PATH.
export PATH=${SASHOME}/SASEnvironmentManagerAgent/2.5/installer/bin:${PATH}
```

WINDOWS:

```
# This should be changed to the path where SAS was installed.
set SASHOME=C:\PROGRA~1\SASHOME
```

```
# This should be changed to the configuration folder and level for this deployment.
set SASCONFIG=C:\SAS\Config\Lev1
```

```
# This is the base folder where SAS Compliance Solutions and all business units are deployed.
set FCFBASE=C:\SAS\Config\Lev1\Applications\SASComplianceSolutions
```

```
# This should add the location of ANT executable provided in the SAS installation, to the
PATH.
set PATH=%SASHOME%\SASEnvironmentManagerAgent\2.5\installer\bin;%PATH%
```

The **A5Q019** hotfix requires that the WebApps be rebuilt and redeployed. Use the following steps to perform this post-installation task:

Step 1: Re-build Web Applications

Note: For this step to execute correctly, at the very least the Metadata Server must be running. It is okay if all other servers are still running.

1. Invoke the SAS Deployment Manager 9.4.
For UNIX, from `$$SASHOME/SASDeploymentManager/9.4`, execute `sasdm.sh`.
For Windows, from `%SASHOME%\SASDeploymentManager\9.4`, execute `sasdm.exe`.
2. Select a language in the Choose Language box.
3. Select *Rebuild Web Applications*.
4. Select *Configuration Directory* or enter the Configuration Directory and Level that needs to be updated.
5. Specify *Connection Information*, including the sasadm User ID and Password.
6. Select the following WebApps:
SAS Compliance Solutions Mid
7.1
7. Verify the information on the Summary screen and select *Start*.
8. Select *Finish* when the deployment is complete.

This process will update the ear files in `<SASCONFIGDIR>/Web/Staging`. The SAS Deployment Manager will backup the original ear files to the directory below:

`<SASCONFIGDIR>/Web/Staging/Backup`

Step 2: Re-deploy Web Applications

Note: For this step to execute correctly, everything should be running: the Metadata Server, the compute tier servers, and all Mid-Tier web application servers.

1. Invoke the SAS Deployment Manager 9.4.
For UNIX, from `$$SASHOME/SASDeploymentManager/9.4`, execute `sasdm.sh`.
For Windows, from `%SASHOME%\SASDeploymentManager\9.4`, execute `sasdm.exe`.
2. Select a language in the *Choose Language* box.
3. Select *Deploy Web Applications*.
4. Select *Configuration Directory* or enter the Configuration Directory and Level that needs to be updated.
5. Specify *Connection Information*, including the sasadm User ID and Password.

6. Select the following WebApps:
SAS Compliance Solutions Mid
7.1
7. Verify the information on the Summary screen and select *Start*.
8. Select *Finish* when the deployment is complete.

Step 3: Apply New Groups and Capabilities to Metadata (if required)

This step is REQUIRED when installing hotfix 10 (A5Q011), hotfix15 (A5Q018), and hotfix16 (A5Q019). These hotfixes contain changed metadata import data that needs to be applied to the first business unit that was configured when the product was deployed, usually FCFBU1. To configure the mid-tier, you need to execute an Ant script that deploys the `antimny1ndin.app.xml` file, token-substitutes it, and then loads it into the SAS Metadata Server. This step needs to be accomplished one time, for FCFBU1.

1. On the mid-tier server machine, create the folder `$FCFBASE/FCFBU1/configmid`, if it doesn't already exist.
2. Copy `$SASHOME/SASComplianceSolutionsMidTier/7.1/deploy/script/build.xml` there.

3. Create a `build.properties` file with these contents:

```
sashome.dir=/install/SASHome
sasconfig.dir=/install/config/Lev1
jdbc.driver.dir=/install/jdbc/oracle
metadata.user=sasadm@saspw
metadata.password=password
dbms.segkc.userid=FCFBU1
dbms.segkc.passwd=password
```

Note: On Windows platforms, all paths in the ANT property files must use double backslashes, or a single forward slash, in place of the single backslash character. These are both valid examples:

```
sasconfig.dir=C:/install/config/Lev1
sasconfig.dir=C:\\install\\config\\Lev1
```

4. Ensure you are in the `$FCFBASE/FCFBU1/configmid` folder. Configure the Mid-Tier metadata for FCFBU1 using the command:

```
ant hotfix -logfile hotfix16.log
```

Step 4: Reapply Business Unit Datasource Definitions

When the Deployment Manager rebuilds and redeploys the web application WAR file, it overwrites all changes made to the following two files:

```
infrastructure_config.xml
spring-config.properties
```

The files are found in the following folder:

```
$$SASCONFIG/Web/WebAppServer/SASServer8_1/sas_webapps/sas.financialservices.aml.war/  
WEB-INF/spring-config
```

After the Deployment Manager redeploys the web application, only datasource definitions for the first bank (FCFBU1) will exist in the files listed above. You need to reapply the datasource information for the remaining business units back into the files. To do this, you will need to execute the following commands:

For UNIX:

```
cd $FCFBASE/FCFBU2/configmid  
cp $$SASHOME/SASComplianceSolutionsMidTier/7.1/deploy/script/build.xml .  
ant context_xml spring_xml spring_properties -logfile cf1.log
```

For Windows:

```
cd %FCFBASE%\FCFBU2\configmid  
copy %SASHOME%\SASComplianceSolutionsMidTier\7.1\deploy\script\build.xml  
.  
ant context_xml spring_xml spring_properties -logfile cf1 web.log
```

Commented [C(T1)]: Should be -logfile

Perform Step 4 for FCFBU2, FCFBU3, and every other business unit except for the first.

When all business units have been reconfigured, restart the Compliance Solutions Mid-Tier web application server (usually SASServer8_1).

Step 5: Import AML Scenarios Package (if required)

For Hotfix 12, there are changes to AML Scenarios. There is an updated file located on the Compute Tier:

For UNIX:

```
$$SASHOME/SASFoundation/9.4/misc/antimnymcn/deploy/data/AMLScenarios.json
```

For Windows:

```
$$SASHOME\SASFoundation\9.4\antimnymcn\sasmisc\deploy\data\AMLScenarios.json
```

Open a browser session from the compute tier server or copy the file to your local machine and use a local browser. Logon to the Anti-Money Laundering web application as a user that has access to the first business unit and has Scenario Administrator and Rule Administrator capabilities.

Make sure, if you have changed the default AML Scenarios or their parameters, that you back up those changes before you proceed. It is not a good practice to change the default scenarios, but instead we recommend making a copy and modifying the copy so that when hotfixes are applied, none of your customizations are lost or overwritten.

Click **Admin** on the Entity Triage window and then click **Scenarios** on the toolbar. Click **Import**. When prompted for a JSON file to import, click **Choose File** and navigate to the `AMLScenarios.json` file at the location shown above. Click **Import**. A message will be displayed stating that the import is in progress. Wait until a dialog window pops up showing the status of the import. Scroll through the information to make sure there was no failure during import. Click **Close** to finish the import.

Repeat these steps for each business unit on your system.

Step 6: Import CDD Rules Package (if required)

For Hotfix 4, there are changes to CDD which delivers new Beneficial Ownership rules. There is an updated file located on the Compute Tier:

For UNIX:

```
$$SASHOME/SASFoundation/9.4/misc/antimnymcn/deploy/data/CDDRules.json
```

For Windows:

```
$$SASHOME\SASFoundation\9.4\antimnymcn\sasmisc\deploy\data\CDDRules.json
```

Open a browser session from the compute tier server or copy the file to your local machine and use a local browser. Log on to the Anti-Money Laundering web application as a user that has access to the first business unit and has Scenario Administrator and Rule Administrator capabilities.

Make sure, if you have changed the default CDD Rules or their parameters, that you back up those changes before you proceed. It is not a good practice to change the default rules, but instead we recommend making a copy and modifying the copy so that when hotfixes are applied, none of your customizations are lost or overwritten.

Click **Admin** on the Entity Triage window and then click **Rules** on the toolbar. Click **Import**. When prompted for a JSON file to import, click **Choose File** and navigate to the `CDDRules.json` file at the location shown above. Click **Import**. A message will be displayed stating that the import is in progress. Wait until a dialog window pops up showing the status of the import. Scroll through the information to make sure there was no failure during import. Click **Close** to finish the import.

Repeat these steps for each business unit on your system.

Concluding Steps:

For security reasons, you should modify your `build.properties` file to erase any clear text passwords stored in the file.

All users when logging on to the AML application for the first time after the hotfix was applied should clear the browser cache to make sure that any data that has been cached by the browser is discarded. Clear cache instructions are browser specific and can be found in the browser documentation or in the Help pages.

This concludes the metadata update portion of the mid-tier configuration.

A6A006 Updates SAS Compliance Solutions LASR Configuration 7.1

Important Note: For ease of completion of post-installation tasks, you can set the following environment variables:

For UNIX:

```
# This should be changed to the path where SAS was installed.  
export SASHOME=/install/SASHome
```

```

# This should be changed to the configuration folder and level for this deployment.
export SASCONFIG=/install/config/Lev1

# This is the base folder where SAS Compliance Solutions and all business units are deployed.
export FCFBASE=${SASCONFIG}/Applications/SASComplianceSolutions

# This will add the location of the SAS ant executable to the PATH.
export PATH=${SASHOME}/SASEnvironmentManagerAgent/2.5/installer/bin:${PATH}

For WINDOWS:
# This should be changed to the path where SAS was installed.
set SASHOME=C:\PROGRA~1\SASHOME

# This should be changed to the configuration folder and level for this deployment.
set SASCONFIG=C:\SAS\Config\Lev1

# This is the base folder where SAS Compliance Solutions and all business units are deployed.
set FCFBASE=C:\SAS\Config\Lev1\Applications\SASComplianceSolutions

# This should add the location of ANT executable provided in the SAS installation, to the
PATH.
set PATH=%SASHOME%\SASEnvironmentManagerAgent\2.5\installer\bin;%PATH%

```

The **A6A006** hotfix does not require any additional configuration.

The **A6A005** hotfix does not require any additional configuration.

The **A6A004** hotfix contains changed files that need to be applied to every business unit that is configured; for example: FCFBU1, FCFBU2, and FCFBU3. The following steps must be repeated for each business unit, substituting the business unit name wherever you see 'FCFBU1' in the steps below.

Execute these steps for the first business unit, then change to the second business unit's **configrpt** folder and execute the steps for the second business unit. Repeat as necessary until all business units have been configured.

1. Create the `$(FCFBASE)/FCFBU1/configrpt` folder and change directory to that folder:

```

For UNIX:
mkdir FCFBASE/FCFBU1/configrpt
cd $(FCFBASE)/FCFBU1/configrpt

```

```

For Windows:
mkdir %FCFBASE%\FCFBU1\configrpt
cd %FCFBASE%\FCFBU1\configrpt

```

2. Copy the `cslasrc.properties` file from <FCFBASE>.

```

For UNIX:
cp $(FCFBASE)/cslasrc.properties $(FCFBASE)/FCFBU1/configrpt

```

```

For Windows:
copy %FCFBASE%\cslasrc.properties %FCFBASE%\FCFBU1\configrpt

```

3. Copy the `build.xml` file from the `SASComplianceSolutionsLASRConfiguration` folder:

For UNIX:

```
cp $SASHOME/SASComplianceSolutionsLASRConfiguration/\
7.1/Configurable/deploy/script/build.xml .
```

For Windows:

```
copy %SASHOME%\SASComplianceSolutionsLASRConfiguration\^
7.1\Configurable\deploy\script\build.xml
```

Create a file in the current directory called `build.properties` and add the following properties to the file:

```
host.name=machine.company.com
```

The `host.name` value above must refer to the middle tier server.

Because of a defect in the software deployment wizard that causes it to write 8 extra spaces to the value of `dbms.segkc.userid` in the `cslasrc.properties` file, you need to provide a property in the `build.properties` file to override it with a value that contains no trailing spaces:

```
dbms.segkc.userid=FCFBU1
```

If you are configuring an Oracle database, make the following additions to the `build.properties` file:

```
dbms.engine=oracle
dbms.oracle.sid=ORCL
dbms.oracle.servicename=ORCL.COMPANY.COM
dbms.system.userid=system
dbms.system.password=password
dbms.core.userid=FCFCORE
dbms.kc.userid=FCFKC
dbms.segkc.userid=FCFBU1
```

If you are configuring a DB2 database, make the following additions to the `build.properties` file:

```
dbms.engine=db2 dbms.database=database dbms.system.userid=db2admin
```

If you are configuring a Teradata database, make the following additions to the `build.properties` file:

```
dbms.engine=Teradata
dbms.host=dbms.company.com
dbms.teradata.database=database
dbms.system.userid=dbc
dbms.teradata.perm.size=100000000
dbms.teradata.spool.size=50000000
```

If you are configuring a SQLServer database, make the following additions to the `build.properties`:

```
dbms.engine=odbc
dbms.sqlserver.instance=database
dbms.system.userid=sa
```

If the metadata server is located on a different machine from the mid-tier server, make the following additions to the `build.properties` file:

```
metadata.host=metadata.company.com
```

If the metadata server operates on a different port from the default, specify the changed port number in the `build.properties` file:

```
metadata.port=9999
```

4. Execute **ant** to configure the report files and create empty extraction datasets:

```
ant -logfile reports.log
```

5. Validate that the reporting installer created empty report data sets. You

can confirm that the reporting installer ran correctly by looking in

`$$SASCONFIG/AppData/SASComplianceSolutions/FCFBU1/AutoLoad`. The following files should be there:

```
active_headers_data.sas7bdat
alert_investigation_extract.sas7bdat
cs_user_info_groups.sas7bdat

jobs_stats_detail.sas7bdat
jobs_stats_summary.sas7bdat
list_report_data.sas7bdat
risk_classifier_report_data.sas7bdat
scenario_audit.sas7bdat
scenario_change_history_data.sas7bdat
scenarios_and_risk_data.sas7bdat
user_group_role_totals.sas7bdat
```

6. Execute `$FCFBASE/FCFBU1/AutoLoad/runsas.sh`, to upload empty datasets to LASR.

Validate that the Autoload program executed correctly and copied the datasets to LASR. The Autoload log file is located in `$FCFBASE/FCFBU1/AutoLoad/Logs`.

7. For security reasons, you should modify your `build.properties` file to erase any clear text passwords stored in the file.

This concludes the LASR configuration portion of the configuration.

A6H004 Updates SAS Compliance Solutions Mid-Tier LASR Configuration 7.1

The **A6H004** hotfix does not require any additional configuration.

The **A6H003** hotfix does not require any additional configuration.

The **A6H002** hotfix contains an updated version of the AMLReports.spk file located in the following folder:

```
$SASHOME/SASComplianceSolutionsMidTierLASRConfiguration/7.1/Config/Deployment/Packages
```

From SAS Metadata Console, you need to re-import the AMLReports.spk package. For more detailed information on how to accomplish this, refer to the SAS Anti-Money Laundering 7.1: Installation and Configuration Guide, under Post-Configuration in the section “Configure Report Tier,” step 5.

This concludes the Mid-Tier LASR configuration portion of the configuration.